

Technical features












706010

TECH MINI COMPACT 03 SQUARE

Square downlight for outdoor surface installation on the ceiling, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 1 x COB "CXA 1507" CREE LED. IP65 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-------------------|--------------------|----------------------|---------------------------|
| 3000°K warm-white | | | |
| cob led | 30° | 637 | 63.70 |

Finish color options:



Technical data

| | · - | |
|--------------|--------------------------------------------------------------------|--|
| Wattage | 10 WATT | |
| IP Rating | IP65 | |
| IK Rating | IK08 | |
| Material | High corrosion resistance die-cast copper-free aluminum body | |
| Coating | Polyester powder coating with phosphocromating pre-finish | |
| Light source | NR. 1 x 9W COB CREE "CXA 1507" LED | |
| Screws | Stainless steel | |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in | |
| Gasket | Silicone rubber | |
| Power cable | 0.5 mt. neoprene power cable included | |
| Glass | Tempered | |
| Gross weight | 1,00 Kg | |
| | | |

