

Technical features



Technical data

20 WATT

IK09

Remote driver 24V DC NEEDED

IP68 - 1 METERS DEPTH

NR. 1x20W COB LED

Stainless steel

Silicone rubber

with nickel-coated

Tempered

included

2,00 Kg

Completely made in stainless steel AISI 316 L marine grade

PG11 Cable gland made copper

3 mt. neoprene power cable

Wattage

IP Rating

IK Rating

Material

Gasket

Glass

Light source Screws

Cable gland

Power cable

Gross weight










305003

Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.





THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
3000°K warm-white				
cob led	30°	1.478	73.90	

Finish color options:



Stainless Steel

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	30°	1.478	73.90

remote driver selection							
brand	manufacturer code	type	watt	IP rate	numbers of fixtures		
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	1		
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	min 1 - max 2		
Meanwell	LPV-100-24	constant voltage 24V DC	120W	IP67	min 1 - max 4		

LAZENO

