


804007

Square pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	1.300	92.86
high-power led	30°	1.230	87.86
high-power led	45°	1.170	83.57

^{*} Other light colors available on request: Neutral-White

Finish color options:







Technical features











Technical data

Wattage	14 WATT	
IP Rating	IP65	
IK Rating	IK09	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Screws	Stainless steel	
Light source	NR. 5 CREE "XP-L" LED	
Gasket	Silicone rubber	
Glass	Tempered	
Transformer	Electronic transformer 220/240V 50/60Hz included	
Power cable	3 m neoprene power cable included	
	3,80 Kg	

