


402604

Designed by MOMO DESIGN

Up & down wall applique for outdoor installation. Phosphochromatised and polyester powder coated copper-free extruded aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 2 x 1 COB CREE "CXB 1512" LED. IP 65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	14°	2 x 1.951	130.06
cob led	35°	2 x 1.850	123.33
cob led	55°	2 x 1.800	120.00
4000°K neutral-white			_
cob led	14°	2 x 2.240	149.33
cob led	35°	2 x 2.131	142.06
cob led	55°	2 x 2.046	136.40

Finish color options:

Textured Grey RAL 9006

Anthracite Grey RAL 7016



Technical features













Technical data

Wattage	30 WATT		
IP Rating	IP65		
IK Rating	IK09		
Material	High corrosion resistance extruded copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light source	NR. 2 x 1 COB CREE "CXB 1512" LED		
Screws	Stainless steel		
Transformer	Electronic power supply 220/240V 50/60Hz built-in		
Cable gland	M16 rubber grommet		
Gasket	Silicone rubber		
Glass	Tempered		
Power cable	1 mt. neoprene power cable included		
Gross weight	3,50 Kg		





Optional: Opal Glass Diffuser



