




101501

ZEUS MINI

Floodlight for outdoor installation on a façade/wall, with 355° swivel base and allowing horizontal adjustment of +90° / -40°. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets and o-rings, with screws in stainless steel. Swivel joint with graduated scale and mechanical aiming lock. Built-in LED driver, with 4 CREE "XP-G2" LED. IP66 rating.



Technical features



Technical data

| | |
|--------------|--|
| Wattage | 8 WATT |
| IP Rating | IP66 |
| IK Rating | IK09 |
| Material | High corrosion resistance die-cast copper-free aluminum body |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | 4 CREE "XP-G2" LED |
| Screws | Stainless steel |
| Transformer | Electrical power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Glass | Tempered |
| Cable gland | M16 rubber grommet |
| Power cable | Not included |
| Gross weight | 1,50 Kg |



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | 15° | 768 | 96.00 |
| high-power led | 35° | 745 | 93.13 |
| high-power led | 55° | 710 | 88.75 |
| 4000°K neutral-white | | | |
| high-power led | 15° | 788 | 98.50 |
| high-power led | 35° | 765 | 95.63 |
| high-power led | 55° | 730 | 91.25 |

Finish color options:

