




303004

POOL MINI

Swimming-pool underwater luminaire, round shape, wall-recessed, completely made in stainless steel AISI 316L, polypropylene housing for recess. 24V remote driver needed, with 4 OSRAM LED. IP 68 rating.



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|--------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led | M 30° | 415 | 51.87 |

Finish color options:

Stainless Steel

remote driver selection

| brand | manufacturer code | type | watt | IP rate | numbers of fixtures |
|----------|-------------------|-------------------------|------|---------|---------------------|
| Meanwell | LPV-20-24 | constant voltage 24V DC | 20W | IP67 | min 1 - max 2 |
| Meanwell | LPV-35-24 | constant voltage 24V DC | 35W | IP67 | min 1 - max 3 |
| Meanwell | LPV-60-24 | constant voltage 24V DC | 60W | IP67 | min 1 - max 6 |
| Meanwell | LPV-100-24 | constant voltage 24V DC | 100W | IP67 | min 1 - max 11 |

Technical features



NEW

Technical data

| | |
|----------------|--|
| Wattage | 8 WATT |
| IP Rating | IP68 - 1 METERS DEPTH |
| IK Rating | IK09 |
| Material | Completely made in stainless steel AISI 316 L marine grade |
| Trim | Stainless steel AISI 316 L marine grade |
| Light source | NR. 4 x 2W OSRAM LED |
| Screws | Stainless steel |
| Remote driver | 24V DC NEEDED |
| Gasket | EPDM rubber |
| Glass | Tempered |
| Cable gland | PG11 made in nickel-plated brass. |
| Power cable | 2 mt. neoprene power cable included |
| Recess housing | Made in polypropylene |
| Gross weight | 1,30 Kg |



