



Technical features



Technical data


| | |
|----------------|--|
| Wattage | 12 WATT |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Material | High corrosion resistance die-cast copper-free aluminum body, cover in concrete material |
| Coating | Polyester powder coating with phosphochromating pre-finish |
| Light source | Low-power CREE LED |
| Screws | Stainless steel |
| Transformer | Electronic power supply 220/240V 50/60Hz built-in |
| Gasket | Silicone rubber |
| Rubber grommet | M16 Rutaseal® in EPDM |
| Diffuser | Polycarbonate |
| Gross weight | 2,00 Kg |

401711

ECLIPSE MEDIUM ROUND CONCRETE

Designed by PAOLO VILLA

Round wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, cover in concrete material; frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.



| light source* | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|---------------------------------------|-------------------|------------------------|
| 3000°K warm-white | | | |
| low power led | <input checked="" type="radio"/> 360° | 556 | 46.33 |

* Other light colors available on request: Neutral-white

Finish color options:

Concrete Grey