


804005

Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-L LED. IP65 rating.



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	1.300	92.86
high-power led	30°	1.230	87.86
high-power led	45°	1.170	83.57

^{*} Other light colors available on request: Neutral-White

Finish color options:







Technical features











Technical data

Wattage 14 WATT IP Rating IP65 IK Rating IK09 Material High corrosion resistance die-cast copper-free aluminum body Coating Polyester powder coating with phosphocromating pre-finish Screws Stainless steel Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included Weight 3,80 Kg			
IK Rating IK09 Material High corrosion resistance die-cast copper-free aluminum body Coating Polyester powder coating with phosphocromating pre-finish Screws Stainless steel Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Wattage	14 WATT	
Material High corrosion resistance die-cast copper-free aluminum body Coating Polyester powder coating with phosphocromating pre-finish Screws Stainless steel Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	IP Rating	IP65	
die-cast copper-free aluminum body Coating Polyester powder coating with phosphocromating pre-finish Screws Stainless steel Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	IK Rating	IK09	
with phosphocromating pre-finish Screws Stainless steel Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Material	die-cast copper-free	
Light source NR. 5 CREE "XP-L" LED Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Coating	with phosphocromating	
Gasket Silicone rubber Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Screws	Stainless steel	
Glass Tempered Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Light source	NR. 5 CREE "XP-L" LED	
Transformer Electronic transformer 220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Gasket	Silicone rubber	
220/240V 50/60Hz included Power cable 3 m neoprene power cable included	Glass	Tempered	
included	Transformer		
Weight 3,80 Kg	Power cable	· · · · · · · · · · · · · · · · · · ·	
	Weight	3,80 Kg	

