


804001

Round pole-top mounted luminaire for outdoor installation on a pole diam. 60 mm or 76 mm, with downward light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Clamp for pole diam 60 mm or 76 mm included. Built-in LED driver 220-240V 50-60Hz, with 5 CREE XP-G3 LED. IP65 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	10°	720	90.00
high-power led	30°	684	85.50
high-power led	45°	650	81.25
4000°K neutral-white			
high-power led	10°	750	93.75
high-power led	30°	713	89.13
high-power led	45°	677	84.63

Finish color options:

Textured Grey RAL 9006

Anthracite Grey RAL 7016

Matt Black (on request)

Technical features

IP65 IK09 CE YEARS







Technical data

Wattage	8 WATT		
IP Rating	IP65		
IK Rating	IK09		
Material	High corrosion resistance die-cast copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Screws	Stainless steel		
Light source	NR. 5 x 1.5W CREE "XP-G3" LED		
Gasket	Silicone rubber		
Glass	Tempered		
Transformer	Electronic transformer 220/240V 50/60Hz included		
Power cable	3 m neoprene power cable included		
Weight	3,80 Kg		





